

MODEL	FD 25	FD 210	F 350	F 300	F 225	F 230
Type	2 Way	2 Way	3 Way	3 Way	2 Way	2 Way
Crossover Freq.	250 Hz	1.2 KHz	1.7-6.3 KHz	0.8 -5 KHz	2.5 KHz	4.5 KHz
Power (RMS)	600 W	600 W	300 W	300 W	300 W	300 W
Impedance (LF)	4/8 Ohms	4/8 Ohms	8 Ohms	8 Ohms	8 Ohms	8 Ohms
Impedance(HF)	8 Ohms	8 Ohms	8 Ohms	8 Ohms	8 Ohms	8 Ohms
Att.slope	6-12 dB/oct	12 dB/oct	12 dB/oct	12 dB/oct	12 dB/oct	12 dB/oct
HF attenuation	-	0,-3,-6,-9dB	-	-	-	-

MODEL	F 250	F 2XT	F CX2	F 200	F 130	F 100
Type	2 Way	2 Way	2 Way	2 Way	High pass	High pass
Crossover Freq.	1.7 KHz	2 KHz	3.5 KHz	400 Hz	3 KHz	6.3 KHz
Power (RMS)	300 W	300 W	300 W	300 W	300 W	300 W
Impedance (LF)	8 Ohms	8 Ohms	8 Ohms	8 Ohms	-	-
Impedance(HF)	8 Ohms	8 Ohms	8 Ohms	8 Ohms	8 Ohms	8 Ohms
Att.slope	12 dB/oct	6-18 dB/oct	6/18 dB/oct	6/12 dB/oct	18 dB/oct	18 dB/oct
HF attenuation	-	-6 dB	-	-	0, -3 dB	0, -3 dB

MODEL	3 VHI-FI	2 VHI-FI
Type	3 Way	2 Way
Crossover Freq.	0.8 – 5 KHz	3 KHz
Power (RMS)	300 W	300 W
Impedance (LF)	8 Ohms	8 Ohms
Impedance(HF)	8 Ohms	8 Ohms
Att.slope	12/12/6 dB/oct	12 dB/oct
HF attenuation	-	-